



**MINING AND  
CONSTRUCTION**

## **YK Series Vibrating Screen**

Vibrating Screen are used to separate materials into various sizes for further processing. Or for end use. Depending on our need. The material is separated by passing it through a vibrating “screen box” which has a number of different sized screens, or meshes, which the material falls through like a sieve, the material falls onto attached conveyors which stock pile the end products. The end products can then be used in the building and construction industries.



#### **Vibrating Screen Features:**

- 1) High screening efficiency
- 2) High capacity and reliability
- 3) Long bearing lifetime
- 4) Easy maintenance

**Vibrating Screen Technical Data:**

Type	ScreenSpec (mm)	Screen Deck	Screen Mesh (mm)	Feeder Opening (mm)	Capacity (t/h)	Power (kw)	Vibrating Frquency (r/min)	Double Amplitude (mm)
2YK1237	1200x3700	2	4~50	≤200	10~80	15	960	4~8
3YK1237	1200x3700	3	4~50	≤200	10~80	15	960	4~8
2YK1548	4800x1500	2	3~100	≤400	30~275	15	870	5~9
3YK1548	4800x1500	3	3~100	≤400	30~275	15	870	5~9
4YK1548	4800x1500	4	3~100	≤400	30~275	15	870	5~9
2YK1848	4800x1800	2	3~100	≤400	56~330	18.5	870	5~9
3YK1848	4800x1800	3	3~100	≤400	56~330	18.5	870	5~9
4YK1848	4800x1800	4	3~100	≤400	56~330	18.5	870	5~9
2YK1860	6000x1800	2	3~100	≤400	65~586	22	870	5~9
3YK1860	6000x1800	3	3~100	≤400	65~586	22-30	870	5~9
4YK1860	6000x1800	4	3~100	≤400	65~586	22-30	870	5~9
2YK2160	6000x2100	2	3~100	≤400	81~720	30	730	5~9
3YK2160	6000x2100	3	3~100	≤400	81~720	30~37	730	5~9
4YK2160	6000x2100	4	3~100	≤400	81~720	45	730	5~9
2YK2460	6000x2400	2	3~150	≤400	100~810	37	770	5~9
3YK2460	6000x2400	3	3~150	≤400	100~810	37	770	5~9



**SHANGHAI ZENITH MINING AND CONSTRUCTION MACHINERY CO., LTD.**

////////////////////////////////////  
No.416 Jianye Road, South Jinqiao Area, Pudong, Shanghai, China .

TEL:0086-21-58386256 0086-21-58386258

FAX:0086-21-58385887

EMAIL:info@zenithcrusher.com

 [www.zenithcrusher.com](http://www.zenithcrusher.com)